

# BX17 MOD Modulock Bench System



BX17 MOD1-U  
Modulock Horseshoe  
Bench System.

BX17 MOD1-U  
Modulock S-  
shape Bench  
configuration.


The Modulock Bench System offers very cost effective modular seating by using standard board sections which can be straight, mitred for corners, or curved in six different radii.

A wide range of interesting shapes can be made by combining standard board sections to make circles, part circles, squares, horseshoes, ovals, snakes and more complex arrangements.

The standard frames are of three types: intermediate frames, end frames and corner frames. Intermediate frames and corner frames have wider head-plates to take two sets of boards. End frames are inset by 50mm from the end of the board section when linear arrangements are specified.

- Boards 32 x 145mm or 45 x 145mm in iroko as standard
- Standard straight board sections are 1000mm long
- Standard mitred corner board sections are 1200mm long
- Boards in iroko, seasoned American oak, or treated softwood

- Legs 60 x 3mm circular hollow, (76 x 2mm in stainless)
- Seat height 482mm, seat width 336mm
- Supplied with extended legs for concreting in as standard (base plate fixing £POA)



Standard Size	Clear internal radius (mm)	Total internal circumference (mm)	Total external circumference (mm)	No. of board sections per complete circle	No. of degrees per section	Board length per section Internal (mm)	Board length per section External (mm)
0	464	2915	5027	6	60	455	791
1	650	4084	6195	8	45	488	745
2	1000	6283	8394	12	30	508	682
3	1500	9424	11535	16	22.5	576	707
4	2000	12566	14677	20	18	616	721
5	2500	15708	17819	24	15	642	730

Standard size board section dimensions

OTHER CONFIGURATIONS AND DIMENSIONS AVAILABLE £POA

telephone: 01782 564411 fax: 01782 565357/562546